# Dell PowerEdge T360

## Technical Guide

Regulatory Model: E78S Series
Regulatory Type: E78S002
March 2024
Rev. A02

DELL Technologies

## Notes, cautions, and warnings

**NOTE:** A NOTE indicates important information that helps you make better use of your product.

**CAUTION: A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.**

**WARNING: A WARNING indicates a potential for property damage, personal injury, or death.**

© 2023 Dell Inc. or its subsidiaries. All rights reserved. Dell Technologies, Dell, and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners.

# Contents

**Chapter 1: Dell PowerEdge T360 system overview....5**
New technologies....5
Key workloads....6

**Chapter 2: Product comparison....7**

**Chapter 3: Chassis views and features....10**
Chassis views....10
Front view of the system....10
Rear view of the system....14
Inside the system....18
Quick Resource Locator....18

**Chapter 4: Processor....20**
Processor features....20
Supported processors....20

**Chapter 5: Memory subsystem....21**
Supported memory....21

**Chapter 6: Storage....22**
Storage controllers....22
Supported Drives....22
Internal storage configuration....23
External Storage....23

**Chapter 7: Networking....24**
Overview....24
Supported network cards....24

**Chapter 8: PCIe subsystem....25**
PCIe risers....25

**Chapter 9: Power, thermal, and acoustics....27**
Power....27
PSU specifications....28
Thermal....29
Thermal design....29
Acoustics....30
PowerEdge acoustical specifications....30
Acoustical configurations of T360....37

**Chapter 10: Operating Systems and Virtualization....39**

Supported Operating Systems....39

**Chapter 11: Dell OpenManage Systems Management....40**
Integrated Dell Remote Access Controller (iDRAC)....40
Systems Management software support matrix....41

**Chapter 12: Appendix D: Service and support....43**
Default support levels....43
Default deployment levels....43
Other services and support information....43
Dell deployment services....43
Dell custom deployment Services....47
Dell Residency Services....47
Dell Data Migration Services....47
Dell Enterprise Support Services....48
Enterprise connectivity....50
Dell TechDirect....51
Dell Technologies Consulting Services....51

**Chapter 13: Appendix A: Additional specifications....53**
Chassis dimensions....53
System weight....54
NIC port specifications....54
Video specifications....54
USB Ports....55
PSU rating....55
Environmental specifications....56
Thermal restriction matrix....57
Thermal air restrictions....58

**Chapter 14: Appendix A. Standards compliance....59**

**Chapter 15: Appendix C Additional resources....60**

1

# Dell PowerEdge T360 system overview

The PowerEdge T360 system is a single-socket 4.5U tower server that supports:

- One Intel Xeon E-2400 series processor with up to eight cores or Intel Pentium G7400/ G7400T processor with up to two cores
- Four UDIMM slots
- A Cabled AC or two redundant AC or DC power supply units
- Up to 8 x 3.5-inch SAS/SATA HDD/SSD drives
- Up to 4 x 3.5-inch SATA HDD/SSD drives
- Up to 8 x 2.5-inch SAS/SATA HDD/SSD drives with 3.5-inch to 2.5-inch adapter

**NOTE:** All instances of SAS and SATA drives are referred to as drives in this document, unless specified otherwise.

**CAUTION: Do not install GPUs, network cards, or other PCIe devices on your system that are not validated and tested by Dell. Damage caused by unauthorized and invalidated hardware installation will null and void the system warranty.**

**Topics:**


- New technologies
- Key workloads


## New technologies

**Table 1. New technologies**

| Technology | Detailed Description |
|---|---|
| Intel Xeon E-2400 series processor | Core count: Up to eight core processor |
| | Maximum number of PCIe lanes: Integrated 16 PCIe Gen5 lanes @ 32 GT/s, 4 PCIe Gen4 lanes @ 16 GT/s |
| | Maximum TDP: 95 W |
| Intel Pentium G7400/ G7400T processor | Core count: Up to two core processor |
| | Maximum number of PCIe lanes: Integrated 16 PCIe Gen5 lanes @ 32 GT/s, 4 PCIe Gen4 lanes @ 16 GT/s |
| | Maximum TDP: 46 W |
| 4400 MT/s DDR5 Memory | Max 4 DIMMs |
| | Supports DDR5 ECC UDIMM |
| Flex I/O | Onboard LOM board, 2x1Gb with BCM5720 LAN controller |
| | Rear I/O with:<br>• 1 x Dedicated iDRAC Ethernet port<br>• 3 x USB 3.2 Gen1<br>• 3 x USB 2.0<br>• 1 x VGA port |
| | Serial Port |

**Table 1. New technologies (continued)**

| Technology | | Detailed Description |
|---|---|---|
| | | Front I/O with:<br>● 1 x USB 3.2 Gen1<br>● 1x iDRAC Direct (Micro-AB USB) port |
| CPLD 1-wire | | Support payload data of PERC, BP, and Rear I/O to BOSS-N1 and iDRAC. |
| Dedicated PERC | | PERC adapters with PERC11 |
| Software RAID | | Operating system RAID/S160 |
| Power Supplies | 60 mm dimension PSU | Platinum 600 W AC/VDC |
| | | Titanium 700 W AC/VDC |
| | 106 mm dimension PSU | Platinum 450 W AC |

# Key workloads

The DellPowerEdgeT360 is versatile enough to address many customer segments and workloads affordably, that includes:

- Collaboration/Sharing: Built-in features to enable collaborative applications between groups of people that share information and processes on-site or remotely
- ROBO Business/Database: Provide computing performance for ROBO business and database workloads including mailing, data process and analysis
- Near Edge: Suitable form-factor for near-edge computing with GPU applications, such as video and audio analysis, surveillance, and VDI

# 2

# Product comparison

The following table shows the comparison between the PowerEdge T360 with the PowerEdge T350.

**Table 2. Features comparison**

| Features | PowerEdge T360 | PowerEdge T350 |
|---|---|---|
| Processor | Maximum one Intel® Xeon® E-2400 series processor with up to eight cores or Intel Pentium G7400/ G7400T processorwith up to two cores | Maximum one Intel® Xeon® E-2300 series processor with up to eight cores, or Intel Pentium processors with up to two cores |
| Memory | DIMM Speed<br>• Up to 4400 MT/s<br>Memory Type<br>• UDIMM<br>Memory module slots<br>• Four DDR5 DIMM slots<br>• Supports unregistered ECC DDR5 DIMM slots only<br>Maximum RAM<br>• UDIMM 128 GB | DIMM Speed<br>• Up to 3200 MT/s<br>Memory Type<br>• UDIMM<br>Memory module slots<br>• Four DDR4 DIMM slots<br>• Supports unregistered ECC DDR4 DIMM slots only<br>Maximum RAM<br>• UDIMM 128 GB |
| Storage Controllers | • Internal controllers: PERC H355 Adapter, PERC H755 Adapter, HBA355i Adapter<br>• Internal Boot: Boot Optimized Storage Subsystem (BOSS-N1): HWRAID 2 x M.2 NVMe SSDs drives, or USB<br>• External HBA (non-RAID): HBA355e Adapter<br>• Software RAID:S160 | • Internal controllers: PERC H345, PERC H355, HBA355i, PERC H755<br>• Internal Boot: Boot Optimized Storage Subsystem (BOSS-S2): HWRAID 2 x M.2 SSDs<br>• External HBA (non-RAID): HBA355e<br>• Software RAID: S150 |
| Drive Bays | Front bays:<br>• Up to 4 x 3.5-inch SATA HDD/SSD, max 64 TB<br>• Up to 8 x 3.5-inch SAS/SATA HDD/SSD, max 128 TB<br>• Up to 8 x 2.5 inch SAS/SATA HDD/SSD with adapter, max 61.44 TB<br>**NOTE:** Supports 2.5-inch drive in 3.5-inch hybrid drive carrier. | Front bays:<br>• Up to 8 x 3.5-inch SAS/SATA (HDD/SSD)<br>• Maximum capacity 160 TB on 8 HDD configuration<br>**NOTE:** Supports 2.5-inch drive in 3.5-inch hybrid drive carrier. |
| Power Supplies | • 450 W AC Platinum 100-240 V AC. Cabled.<br>• 600 W Platinum 100-240 V AC or 600 W 240 HVDC, hot swap redundant.<br>• 700 W Titanium 200-240 VAC or 700 W 240 HVDC, hot swap redundant. | • 450 W AC only Bronze 100-240 V AC. Cabled.<br>• 600 W Mixed Mode Platinum 100-240 V AC or 240 V DC. Hot swap redundant.<br>• 700 W Mixed Mode Titanium 200-240 V AC or 240 V DC. Hot swap redundant. |
| Cooling Options | Air cooling | Air Cooling |
| Fans | Standard (STD) fan and one optional High performance (HPR) fan | Standard (STD) fans /High performance (HPR) silver fans |
| | Up to two cabled fans | Up to one cabled fan |
| Dimension | Height: 382.5 mm (15.05 inches) (with feet) | Height: 382.5 mm (15.05 inches) (with feet) |

**Table 2. Features comparison (continued)**

| Features | PowerEdge T360 | PowerEdge T350 | |
|---|---|---|---|
| | 369.5 mm (14.54 inches) (without feet) | 369.5 mm (14.54 inches) (without feet) | |
| | Width—175.0 mm (6.88 inches) | Width—175.0 mm (6.88 inches) | |
| | Depth—579.72 mm (22.82 inches) (with bezel) | Depth—579.72 mm (22.82 inches) (with bezel) | |
| | 562.12 mm (22.13 inches) (without bezel) | 562.12 mm (22.13 inches) (without bezel) | |
| Form Factor | 4.5U tower server | 4.5U tower server | |
| Embedded Management | • iDRAC9 Enterprise<br>• iDRAC Direct<br>• Datacenter license options<br>• iDRAC RESTful API with Redfish<br>• iDRAC Service Module | • iDRAC9<br>• iDRAC Direct<br>• iDRAC RESTful API with Redfish<br>• iDRAC Service Module | |
| Bezel | Security bezel | Optional LCD bezel or security bezel | |
| OpenManage Software | • OpenManage Enterprise<br>• OpenManage Power Manager plugin<br>• OpenManage Service plugin<br>• OpenManage Update Manager plugin<br>• CloudIQ for PowerEdge plug in<br>• OpenManage Enterprise Integration for VMware vCenter<br>• OpenManage Integration for Microsoft System Center<br>• OpenManage Integration with Windows Admin Center | • OpenManage Enterprise<br>• OpenManage Power Manager plug-in<br>• OpenManage SupportAssist plug-in<br>• OpenManage Update Manager plug-in | |
| Mobility | OpenManage Mobile | OpenManage Mobile | |
| Integrations and Connections | • BMC Truesight<br>• Microsoft System Center<br>• OpenManage Integration with ServiceNow<br>• Red Hat Ansible Modules<br>• Terraform Providers<br>• VMware vCenter and vRealize Operations Manager | OpenManage Integrations<br>• BMC Truesight<br>• Microsoft System Center<br>• Red Hat Ansible Modules<br>• VMware vCenter and vRealize Operations Manager | OpenManage Connections<br>• IBM Tivoli Netcool/ OMNIbus<br>• IBM Tivoli Network Manager IP Edition<br>• Micro Focus Operations Manager<br>• Nagios Core<br>• Nagios XI |
| Security | • Cryptographically signed firmware<br>• Data at Rest Encryption (SEDs with local or external key mgmt)<br>• Secure Boot<br>• Secured Component Verification (Hardware integrity check)<br>• Secure Erase<br>• Secured-core server<br>• Silicon Root of Trust<br>• System Lockdown (requires iDRAC9 Enterprise or Datacenter)<br>• TPM 2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ | • Cryptographically signed firmware<br>• Secure Boot<br>• Secure Erase<br>• Silicon Root of Trust<br>• System Lockdown (requires iDRAC9 Enterprise or Datacenter)<br>• TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ | |
| Embedded NIC | 2 x 1 GbE LOM | 2 x 1 GbE LOM | |

**Table 2. Features comparison (continued)**

| Features | PowerEdge T360 | | PowerEdge T350 | |
|---|---|---|---|---|
| Networking Options | Optional Network Card | | Optional Network Card | |
| GPU Options | Up to one single-width 60 W accelerator | | Not supported | |
| Ports | Front Ports<br>• 1 x USB 3.2 Gen1<br>• 1 x iDRAC Direct (Micro-AB USB) port | Rear Ports<br>• 3 x USB 2.0<br>• 3 x USB 3.2 Gen1<br>• 1 x Serial port<br>• 1 x Dedicated iDRAC Ethernet port<br>• 2 x Ethernet port<br>• 1 x VGA port | Front Ports<br>• 1 x iDRAC Direct (Micro-AB USB) port<br>• 1 x USB 3.0 | Rear Ports<br>• 5 x USB 2.0<br>• 1 x iDRAC ethernet port<br>• 1 x USB 3.0<br>• 1 x VGA<br>• 1 x Serial |
| | Internal Port :<br>• 1 x USB 3.2 Gen1 | | Internal Port :<br>• 1 x USB 3.0 (Optional) | |
| PCIe | Slot 1: x8 Gen4 Full height, half length | | Slot 1: x8 Gen4 Full height, half length | |
| | Slot 2: x16 Gen5 Full height, half length | | Slot 2: x16 Gen4 Full height, full length | |
| | Slot 3: x1 Gen4 Full height, half length | | Slot 3: x1 Gen3 Full height, half length | |
| | Slot 4: x8 Gen4 Full height, half length | | Slot 4: x8 Gen3 Full height, half length | |
| Operating System and Hypervisors | • Canonical Ubuntu Server LTS<br>• Microsoft Windows Server with Hyper-V<br>• Red Hat Enterprise Linux<br>• SUSE Linux Enterprise Server<br>• VMware ESXi<br>For specifications and interoperability details, see Dell.com/OSsupport. | | • Canonical Ubuntu Server LTS<br>• VMware ESXi<br>• Microsoft Windows Server with Hyper-V<br>• SUSE Linux Enterprise Server<br>• Red Hat Enterprise Linux<br>For specifications and interoperability details, see Dell EMC Enterprise Operating Systems on Servers, Storage, and Networking page at Dell.com/OSsupport. | |

**NOTE:** HVDC stands for High-Voltage DC, with 336 V DC.

# 3

# Chassis views and features

**Topics:**

- Chassis views

## Chassis views

### Front view of the system





**Figure 1. Front view of 4 x 3.5-inch drive system**

### Table 3. Features available on the front of the system

| Item | Ports, panels, and slots | Icon | Description |
|---|---|---|---|
| 1 | Power button | | Indicates if the system is powered on or off. Press the power button to manually power on or off the system. |
| 2 | Status LED indicators | | Indicates the status of the system. For more information, see the Status LED indicators section. |
| 3 | Express Service Tag | N/A | A slide-out label panel that contains the Express Service Tag that has system information such as Service Tag, NIC, MAC address, and so on. If you have opted for the secure default access to iDRAC, the Information tag will also contain the iDRAC secure default password. |
| 4 | USB 3.2 port | | Supports USB 3.2 compliant devices |
| 5 | iDRAC Direct (Micro-AB USB) port | | The iDRAC Direct (Micro-AB USB) port enables you to access the iDRAC direct Micro-AB USB features. For more information, see the Integrated Dell Remote Access Controller User's Guide at PowerEdge Manuals. |
| 6 | Optical drive | N/A | Enables you to retrieve and store data on optical discs such as compact discs (CD) and digital versatile discs (DVD). For more information, see the Technical specifications section. |
| 7 | Drive Bay | N/A | Enables you to install SAS/SATA drives that are supported on your system. |
| 8 | BOSS-N1 (optional) | N/A | BOSS-N1 (optional) for internal system boot. |





**Figure 2. Front view of 8 x 3.5-inch drive system**

## Table 4. Features available on the front of the system

| Item | Ports, panels, and slots | Icon | Description |
|---|---|---|---|
| 1 | Power button | ⏻ | Indicates if the system is powered on or off. Press the power button to manually power on or off the system. |
| 2 | Status LED indicators | 🛈 | Indicates the status of the system. For more information, see the Status LED indicators section. |
| 3 | Express Service Tag | N/A | A slide-out label panel that contains the Express Service Tag that has system information such as Service Tag, NIC, MAC address, and so on. If you have opted for the secure default access to iDRAC, the Information tag |

**Table 4. Features available on the front of the system (continued)**

| Item | Ports, panels, and slots | Icon | Description |
|---|---|---|---|
| | | | will also contain the iDRAC secure default password. |
| 4 | USB 3.2 port |  | Supports USB 3.2 compliant devices |
| 5 | iDRAC Direct (Micro-AB USB) port |  | The iDRAC Direct (Micro-AB USB) port enables you to access the iDRAC direct Micro-AB USB features. For more information, see the Integrated Dell Remote Access Controller User's Guide at PowerEdge Manuals. |
| 6 | Optical drive | N/A | Enables you to retrieve and store data on optical discs such as compact discs (CD) and digital versatile discs (DVD). For more information, see the Technical specifications section. |
| 7 | Drive Bay | N/A | Enables you to install SAS/SATA drives that are supported on your system. |
| 8 | BOSS-N1 (optional) | N/A | BOSS-N1 (optional) for internal system boot. |

# Rear view of the system





**Figure 3. Rear view of the system**

## Table 5. Features available at the rear of the system

| Item | Ports, panels, or slots | Icon | Description |
|---|---|---|---|
| 1 | Power supply unit (PSU 1) | 1 | PSU1 is the primary PSU of the system. |
| 2 | Power supply unit (PSU 2) | 2 | PSU2 is the secondary PSU of the system. |
| 3 | PCIe expansion card slots (4) | N/A | Enables you to connect PCI express expansion cards. |
| 4 | 2 x USB 2.0 + 2 x USB 3.2 ports | | Supports USB 2.0 and USB 3.2 compliant devices. |
| 5 | System Identification (ID) button | | The System Identification (ID) button is available at the rear of the system. Press the button to identify a system by turning on the system ID button. You can also use the system ID button to reset |

**Table 5. Features available at the rear of the system (continued)**

| Item | Ports, panels, or slots | Icon | Description |
|---|---|---|---|
| | | | iDRAC and to access BIOS using the step-through mode. When pressed, the system ID LED in the back panel blinks until either the front or rear button is pressed again. Press the button to toggle between on or off mode. |
| 6 | NIC port (2) | | The NIC ports that are integrated on the LOM card provide network connectivity which is connected to the system board. |
| 7 | USB 3.2 port | | Supports USB 3.2 compliant devices. |
| 8 | NIC port (1) | | The NIC ports that are integrated on the LOM card provide network connectivity which is connected to the system board. |
| 9 | USB 2.0 port | | Supports USB 2.0 compliant devices. |
| 10 | Dedicated iDRAC Ethernet port | iDRAC | Enables you to remotely access iDRAC. For more information, see the Integrated Dell Remote Access Controller User's Guide at PowerEdge Manuals. |
| 11 | VGA port | | Enables you to connect a display device to the system. |
| 12 | Serial port | | Enables you to connect a serial device to the system. |





**Figure 4. Rear view of the system with cable PSU**

## Table 6. Rear view of the system

| Item | Ports, panels, or slots | Icon | Description |
|---|---|---|---|
| 1 | Cabled power supply unit | | Enables you to connect to AC power source. |
| 2 | PCIe expansion card slots (4) | N/A | Enables you to connect PCI express expansion cards. |
| 3 | 2 x USB 2.0 + 2 x USB 3.2 ports | | Supports USB 2.0 and USB 3.2 compliant devices. |
| 4 | System Identification (ID) button | | The System Identification (ID) button is available at the rear of the system. Press the button to identify a system by turning on the system ID button. You can also use the system ID button to reset iDRAC and to access BIOS using the step-through mode. When pressed, the system ID LED in the back panel blinks until either the front or rear |

**Table 6. Rear view of the system (continued)**

| Item | Ports, panels, or slots | Icon | Description |
|---|---|---|---|
| | | | button is pressed again. Press the button to toggle between on or off mode. |
| 5 | NIC port (2) | | The NIC ports that are integrated on the LOM card provide network connectivity which is connected to the system board. |
| 6 | USB 3.2 port | | Supports USB 3.2 compliant devices. |
| 7 | NIC port (1) | | The NIC ports that are integrated on the LOM card provide network connectivity which is connected to the system board. |
| 8 | USB 2.0 port | | Supports USB 2.0 compliant devices. |
| 9 | Dedicated iDRAC Ethernet port | iDRAC | Enables you to remotely access iDRAC. For more information, see the Integrated Dell Remote Access Controller User's Guide at PowerEdge Manuals. |
| 10 | VGA port | | Enables you to connect a display device to the system. |
| 11 | Serial port | | Enables you to connect a serial device to the system. |

# Inside the system





**Figure 5. Inside view of the 8 x 3.5-inch configuration**

1. PSU
2. System board
3. Intrusion switch
4. Cooling fan
5. Memory module sockets
6. Heat sink
7. Backplane

# Quick Resource Locator

The QRL on everything (SILs, GSG, Owner's Manual except on the EST) is a generic QRL for T360 that leads to a webpage for that product. That webpage has links for things like setup and service videos, iDRAC manual, and other things that apply to the platform. The QRL on the EST is unique and specific to that service tag and will contain the Service Tag number and the iDRAC password. The label and the QRL code within it are printed on demand at the L10 factories. This QRL links to a webpage that shows the exact configuration as built for that customer, and the specific warranty purchased. It is one click away from the same content of generic information that applies to T360 that is available in the other QRLs.




**Figure 6. Quick Resource Locator for PowerEdge T360 system**

# 4

# Processor

**Topics:**

- Processor features

## Processor features

The following lists the features and functions that are in the upcoming Intel® Xeon E-2400 series processor offering:

- For small businesses, Xeon E provides a reliable solution with business-ready servers to support business-critical services and customer data needs.
- For cloud services, Xeon E is the perfect option for Bare Metal Instances & Code/Data Security, with a cost-effective solution for essential performance to support entry-level bare metal services.

Key updates for the E-2400 series include increased performance with a new processor core architecture:

- 4, 6, and 8 core option
- Up to 95 W TDP
- Up to 128 GB memory
- DDR5 up to 4800 MT/s

## Supported processors

The following table shows the processors that are supported on the T360.

**Table 7. Supported processors for T360**

| Processor | Clock Speed (GHz) | Cache (M) | Cores | Threads | Turbo* | Memory Speed (MT/s) | Memory Capacity | TDP |
|---|---|---|---|---|---|---|---|---|
| E-2488 | 3.2 | 24 | 8 | 16 | Turbo | 4800 | 128 GB | 95 W |
| E-2486 | 3.5 | 18 | 6 | 12 | Turbo | 4800 | 128 GB | 95 W |
| E-2478 | 2.8 | 24 | 8 | 16 | Turbo | 4800 | 128 GB | 80 W |
| E-2468 | 2.6 | 24 | 8 | 16 | Turbo | 4800 | 128 GB | 65 W |
| E-2456 | 3.3 | 18 | 6 | 12 | Turbo | 4800 | 128 GB | 80 W |
| E-2436 | 2.9 | 18 | 6 | 12 | Turbo | 4800 | 128 GB | 65 W |
| E-2434 | 3.4 | 12 | 4 | 8 | Turbo | 4800 | 128 GB | 55 W |
| E-2414 | 2.6 | 12 | 4 | 4 | Turbo | 4800 | 128 GB | 55 W |
| G7400 | 3.7 | 6 | 2 | 4 | No Turbo | 4800 | 128 GB | 46 W |
| G7400T | 3.1 | 6 | 2 | 4 | No Turbo | 4800 | 128 GB | 35 W |

**NOTE:** * Intel E-2400 Series processors under turbo mode will not be able to meet max frequency due to processor TDP thermal limitations.

# 5

# Memory subsystem

**Topics:**

- Supported memory

## Supported memory

**Table 8. Memory technology**

| DIMM type | Rank | Capacity | DIMM rated voltage and speed | Operating Speed | |
|---|---|---|---|---|---|
| | | | | 1 DIMM per channel (DPC) | 2 DIMM per channel (DPC) |
| ECC UDIMM | 1 R | 16 GB | DDR5 (1.1 V), 4800 MT/s | 4400 MT/s | 4000 MT/s |
| | 2 R | 32 GB | DDR5 (1.1 V), 4800 MT/s | 4400 MT/s | 3600 MT/s |

The following table lists the supported DIMMs for T360. For the latest information on supported memory and memory configurations reference the latest SDL.

**Table 9. Supported DIMMs**

| Rated DIMM Speed (MT/s) | DIMM Type | DIMM Capacity (GB) | Ranks per DIMM | Data Width | DIMM Volts |
|---|---|---|---|---|---|
| 4800 | UDIMM | 16 | 1 | 8 | 1.1 |
| 4800 | UDIMM | 32 | 2 | 8 | 1.1 |

# 6

# Storage

**Topics:**


- Storage controllers
- Supported Drives
- Internal storage configuration
- External Storage


## Storage controllers

- PowerEdge Hardware RAID controllers (PERC) series 11 is designed for:
  - Enhanced performance
  - Fault tolerance
  - Simplified management of RAID array drives
- PowerEdge controller series 11 supports older legacy SAS and SATA drive interfaces.
- Dell S160 is a software RAID solution for PowerEdge systems.

**Table 10. PERC Series controller offerings**

| Performance Level | Controller and Description |
|---|---|
| Entry | S160 (Software RAID: SATA) |
| Value | H355, HBA355 (internal/external) |
| Performance | H755 |

**NOTE:** For more information about the features of the Dell PowerEdge RAID controllers (PERC), Software RAID controllers, or BOSS cards, and on deploying the cards, see the storage controller documentation at Storage controller manuals.

**NOTE:** H355 replaces H345 as the entry raid controller.

## Supported Drives

**Table 11. Supported Drives**

| Form Factor | Type | Speed | Rotational Speed | Capacities |
|---|---|---|---|---|
| 2.5 inches | vSAS | 12 Gb | SSD | 960 Gb, 1.92 TB, 3.84 TB, 7.68 TB |
| | SAS | 24 Gb | SSD | 800 Gb, 960 GB, 1.6 TB, 1.92 TB, 3.84 TB, 7.68 TB |
| | SATA | 6 Gb | SSD | 480 Gb, 960 Gb, 1.92 TB, 3.84 TB |
| 3.5 inches | SAS | 12 Gb | 7.2 K | 4 TB, 8 TB, 12 TB, 16 TB |
| | SATA | 6 Gb | 7.2 K | 2 TB, 4 TB, 8 TB, 12 TB, 16 TB |

# Internal storage configuration

T360 supports the following internal storage configurations:

- 8 x 3.5 inch (8 x 2.5-inch with HDD adapter) (SAS/SATA) RAID
- 4 x 3.5 inch (SATA)

# External Storage

The T360 supports the external storage device types listed in the table below.

### Table 12. Support External Storage Devices

| Device Type | Description |
|---|---|
| External Tape | Supports connection to external USB tape products |
| NAS/IDM appliance software | Supports NAS software stack |
| JBOD | Supports connection to 12 Gb MD-series JBODs |

# 7

# Networking

**Topics:**


- Overview
- Supported network cards


## Overview

PowerEdge offers a wide variety of options to get information moving to and from our servers. Industry best technologies are chosen, and systems management features are added by our partners to firmware to tie in with iDRAC. These adapters are rigorously validated for worry-free, fully supported use in Dell servers.

## Supported network cards

**Table 13. Supported network cards**

| Vendor | Port type | Port speed | Port count |
|---|---|---|---|
| Broadcom | F1 | 1 GbE | 4 |
| Intel | BT | 10 GbE | 2 |
| Intel | BT | 10 GbE | 4 |
| Broadcom | BT | 10 GbE | 2 |
| Broadcom | BT | 10 GbE | 4 |
| Intel | F1 | 1 GbE | 4 |

# 8

# PCIe subsystem

**Topics:**

- PCIe risers

## PCIe risers

The T360 has a no riser option. Shown below are the riser offerings for the platform.





**Figure 7. Riser connector slots on system board**

1. PCIe Slot 1 (CPU 1)
2. PCIe Slot 2 (CPU 1)
3. PCIe Slot 3 (Platform Controller Hub)
4. PCIe Slot 4 (Platform Controller Hub)

### Table 14. PCIe Riser Configurations

| Config No. | Riser configuration | No. of Processors | PERC type supported | Rear storage possible |
|---|---|---|---|---|
| 0 | N/A | 1 | Adapter | No |

**NOTE:** The expansion-card slots are not hot-swappable.

The following table provides guidelines for installing expansion cards to ensure proper cooling and mechanical fit. The expansion cards with the highest priority should be installed first using the slot priority indicated. All the other expansion cards should be installed in the card priority and slot priority order.

### Table 15. Configuration : No Riser

| Card type | Slot priority | Maximum number of cards |
|---|---|---|
| FOXCONN (GPU) | 2 | 1 |
| FOXCONN (aPERC 11) | 2,1 | 1 |
| FOXCONN (aPERC HBA11) | 2,1 | 1 |
| FOXCONN (External Adapter) | 2,1 | 2 |
| Broadcom (NIC:1Gb) | 2,1,4 | 3 |
| Intel (NIC:10Gb) | 2,1,4 | 3 |
| Broadcom (NIC:10Gb) | 2,1,4 | 3 |
| Intel (NIC:1Gb) | 2,1,4 | 3 |
| FOXCONN (BOSS-N1) | INT | 1 |

# 9

# Power, thermal, and acoustics

PowerEdge servers have an extensive collection of sensors that automatically track thermal activity, which helps to regulate temperature by reducing server noise and power consumption. The table below lists the tools and technologies Dell offers to lower power consumption and increase energy efficiency.

**Topics:**


- Power
- Thermal
- Acoustics


## Power

**Table 16. Power tools and technologies**

| Feature | Description |
|---|---|
| Power Supply Units(PSU) portfolio | Dell's PSU portfolio includes intelligent features such as dynamically optimizing efficiency while maintaining availability and redundancy. Find additional information in the Power supply units section. |
| Tools for right sizing | Enterprise Infrastructure Planning Tool (EIPT) is a tool that can help you determine the most efficient configuration possible. With Dell's EIPT, you can calculate the power consumption of your hardware, power infrastructure, and storage at a given workload. Learn more at Dell EIPT. |
| Industry Compliance | Dell's servers are compliant with all relevant industry certifications and guide lines, including 80 PLUS, Climate Savers and ENERGY STAR. |
| Power monitoring accuracy | PSU power monitoring improvements include:<br>● Dell's power monitoring accuracy is currently 1%, whereas the industry standard is 5%<br>● More accurate reporting of power<br>● Better performance under a power cap |
| Power capping | Use Dell's systems management to set the power cap limit for your systems to limit the output of a PSU and reduce system power consumption. Dell is the first hardware vendor to leverage Intel Node Manager for circuit-breaker fast capping. |
| Systems Management | iDRAC Enterprise and Datacenter provides server-level management that monitors, reports and controls power consumption at the processor, memory and system level.<br>Dell OpenManage Power Center delivers group power management at the rack, row, and data center level for servers, power distribution units, and uninterruptible power supplies. |
| Active power management | Intel Node Manager is an embedded technology that provides individual server-level power reporting and power limiting functionality. Dell offers a complete power management solution comprised of Intel Node Manager accessed through Dell iDRAC9 Datacenter and OpenManage Power Center that allows policy-based management of power and thermal at the individual server, rack, and data center level. Hot spare reduces power consumption of redundant power supplies. Thermal control off a speed optimizes the thermal settings for your environment to reduce fan consumption and lower system power consumption.<br>Idle power enables Dell servers to run as efficiently when idle as when at full workload. |
| Rack infrastructure | Dell offers some of the industry's highest-efficiency power infrastructure solutions, including: |

**Table 16. Power tools and technologies (continued)**

| Feature | Description |
|---|---|
| | • Power distribution units (PDUs)<br>• Uninterruptible power supplies (UPSs)<br>• Energy Smart containment rack enclosures<br>Find additional information at: Power and Cooling. |

# PSU specifications

The PowerEdge T360 system supports up to two AC or DC power supply units (PSUs).

**Table 17. PSU specifications**

| PSU | Class | Heat dissipation (maximum) | Frequency | AC Voltage | | | DC Voltage | | Current |
|---|---|---|---|---|---|---|---|---|---|
| | | | | 100–120 V | 200–240 V | 277 V | 240 V | 336 V | |
| 450 W | Platinum | 1730 BTU/hr | 50/60 Hz | 450 W | 450 W | N/A | N/A | N/A | 6.5 A - 3.5 A |
| 600 W Mixed Mode | Platinum | 2250 BTU/hr | 50/60 Hz | 600 W | 600 W | N/A | N/A | N/A | 7.1 A - 3.6 A |
| | N/A | 2250 BTU/hr | N/A | N/A | N/A | N/A | 600 W | N/A | 2.9 A |
| 700 W Mixed Mode | Titanium | 2625 BTU/hr | 50/60 Hz | N/A | 700 W | N/A | N/A | N/A | 4.1 A |
| | N/A | 2625 BTU/hr | N/A | N/A | N/A | N/A | 700 W | N/A | 3.4 A |

**NOTE:** This system is also designed to connect to the IT power systems with a phase-to-phase voltage not exceeding 240 V.

**NOTE:** Heat dissipation is calculated using the PSU wattage rating.

**NOTE:** When selecting or upgrading the system configuration, to ensure optimum power utilization, verify the system power consumption with the Dell Energy Smart Solution Advisor available at **Dell.com/ESSA**.





**Figure 8. PSU power cord**

**Table 18. PSU power cords**

| Form factor | Output | Power cord |
|---|---|---|
| Cable PSU 106 mm | 450 W AC | C13/C14 |
| Redundant 60 mm | 600 W AC | C13/C14 |
| | 700 W AC | C13/C14 |

# Thermal

PowerEdge servers have an extensive collection of sensors that automatically track thermal activity, which helps regulate temperature thereby reducing server noise and power consumption.

## Thermal design

Thermal management of the platform helps deliver high performance with the right amount of cooling to components, while maintaining the lowest fan speeds possible. This is done across a wide range of ambient temperatures from 10°C to 35°C (50°F to 95°F) and to extended ambient temperature ranges.





**Figure 9. Thermal design characteristics**

The thermal design of the PowerEdge T360 reflects the following:

- Optimized thermal design: The system layout is architected for optimum thermal design.
- System component placement and layout are designed to provide maximum airflow coverage to critical components with minimum expense of fan power.
- Comprehensive thermal management: The thermal control system regulates the fan speed based on several different responses from all system-component temperature sensors, and inventory for system configurations. Temperature monitoring includes components such as processors, DIMMs, chipset, the inlet air ambient, hard disk drives, and OCP.
- Open and closed loop thermal fan speed control: Open loop thermal control uses system configuration to determine fan speed based on inlet air ambient temperature. Closed loop thermal control method uses feedback temperatures to dynamically determine proper fan speeds.
- User-configurable settings: With the understanding and realization that every customer has unique set of circumstances or expectations from the system, in this generation of servers, we have introduced limited user- configurable settings residing in the iDRAC BIOS setup screen. For more information, see the Dell PowerEdge T360 Installation and Service Manual at PowerEdge Manuals and “Advanced Thermal Control: Optimizing across Environments and Power Goals” on Dell.com.
- Cooling redundancy: The T360 allows N+1 fan redundancy, allowing continuous operation with one fan failure in the system.
- Environmental Specifications: The optimized thermal management makes the T360 reliable under a wide range of operating environments.

# Acoustics

## PowerEdge acoustical specifications

For more information about acoustical specifications, see ENG0019663. (See the category definitions.)

Dell typically categorizes servers in five categories of acoustically acceptable usage:

- Category 1: Table-top in Office Environment
- Category 2: Floor-standing in Office Environment
- Category 3: General Use Space
- Category 4: Attended Data Center
- Category 5: Unattended Data Center

### Category 1: Table-top in Office Environment

When Dell determines that a specific Enterprise product is to be used on a table-top in office environment, for example, on a desk around a seated user's head height, and then the acoustical specification of the following table applies. Small, light-weight towers are examples of these types of products.

**Table 19. Dell Enterprise Category 1, "Table-top in Office Environment" acoustical specification category.**

| Measurement Position re AC0158 | Metric, re AC0159 | Test Modes, re AC0159 (note must be in steady state, see AC0159, except where noted below) | | | |
|---|---|---|---|---|---|
| | | Standby in 23±2° C Ambient | Idle in 23±2° C Ambient | Operating in 23±2° C Ambient – if not otherwise specified in the program's configuration document, then processor and hard drive operating modes are required | Simulate (that is, set fan speeds representative) for Idle at 28° C & 35° C Ambient, and for 100% loading and maximum configuration, at 35° C Ambient |
| Sound Power | LwA-m, bels | ≤ 4.2 | ≤ 4.7 | ≤ 5.0 | Report |
| Sound Quality (both positions must meet limits): Front Binaural HEAD and Rear Microphone | Tones, Hz, dB | No prominent tones per criteria D.10.6 and D.10.8 of ECMA-74 | | | Report tones |
| | Tonality, tu | ≤ 0.35 | ≤ 0.35 | ≤ 0.35 | Report |
| | Dell Modulation, % | ≤ 35 | ≤ 35 | ≤ 35 | Report |
| | Loudness, sones | Report | Report | Report | Report |
| | LpA-single point, dBA | Report | Report | Report | Report |
| Front Binaural HEAD | Transients | • Oscillation (see AC0159), if observed, during 20-minute steady-state observation, must adhere to the following two criteria:<br>○ Max. {ΔLpA} < 3.0 dB<br>○ Event count < 3 for "1.5 dB < ΔLpA < 3.0 dB"<br>○ Acoustical Jump (see AC0159), during air mover speed transition from Idle to Operating Mode must be ≤ 15 dB.<br>• Startup behavior<br>○ Report Startup behavior re. AC0159 | | | N/A |

**Table 19. Dell Enterprise Category 1, "Table-top in Office Environment" acoustical specification category. (continued)**

| Measurement Position re AC0158 | Metric, re AC0159 | Test Modes, re AC0159 (note must be in steady state, see AC0159, except where noted below) | | | |
|---|---|---|---|---|---|
| | | **Standby in 23±2° C Ambient** | **Idle in 23±2° C Ambient** | **Operating in 23±2° C Ambient – if not otherwise specified in the program's configuration document, then processor and hard drive operating modes are required** | **Simulate (that is, set fan speeds representative) for Idle at 28° C & 35° C Ambient, and for 100% loading and maximum configuration, at 35° C Ambient** |
| | | ○ Startup must proceed smoothly, that is, no sudden or large jumps, and fan speed during startup must not exceed 50% of its maximum<br>● Transient inputs: Report time-history sound pressure levels re AC0159 "Train of Step Functions on Processor" | | | |
| Any | Other | No rattles, squeaks, or unexpected noises<br>Sound should be "even" around the EUT (one side should not be dramatically louder than another)<br>Unless otherwise specified, the "default" thermal-related settings shall be selected for BIOS and iDRAC.<br>Specific operating conditions will be defined in "Configurations & Configuration Dependencies" for each platform. | | | |
| Sound Pressure | LpA-reported, dBA, re AC0158 and program configuration document | Report for all mics | Report for all mics | Report for all mics | Report for all mics |

## Category 2: Floor-standing in Office Environment

When Dell determines that a specific Enterprise product is to be used primarily when it is sitting on the floor, that is, next to a user's feet, then the acoustical specification in the table below applies. Noise from the product should not annoy or otherwise interfere with the user's thoughts or speech, for example, on the telephone.

### Table 20. Dell Enterprise Category 2, "Floor-standing in Office Environment" acoustical specification category

| Measurement Position re AC0158 | Metric, re AC0159 | Test Modes, re AC0159 (note must be in steady state, see AC0159, except where noted below) | | | |
|---|---|---|---|---|---|
| | | **Standby in 23±2° C Ambient** | **Idle in 23±2° C Ambient** | **Operating in 23±2° C Ambient – if not otherwise specified in the program's configuration document, then processor and hard drive operating modes are required** | **Simulate (that is, set fan speeds representative) for Idle at 28° C & 35° C Ambient, and for 100% loading and maximum configuration, at 35° C Ambient** |
| Sound Power | LwA-m, bels | ≤ 4.9 | ≤ 5.1 | ≤ 5.4 | Report |
| Sound Quality (both positions must meet limits): Front Binaural HEAD and Rear Microphone | Tones, Hz, dB | No prominent tones per criteria D.10.6 and D.10.8 of ECMA-74 | | | Report tones |
| | Tonality, tu | ≤ 0.35 | ≤ 0.35 | ≤ 0.35 | Report |
| | Dell Modulation, % | ≤ 35 | ≤ 35 | ≤ 35 | Report |
| | Loudness, sones | Report | Report | Report | Report |
| | LpA-single point, dBA | Report | Report | Report | Report |
| Front Binaural HEAD | Transients | • Oscillation (see AC0159), if observed, during 20-minute steady-state observation, must adhere to the following two criteria:<br>○ Max. {ΔLpA} < 3.0 dB<br>○ Event count < 3 for "1.5 dB < ΔLpA < 3.0 dB"<br>• Acoustical Jump (see AC0159), during air mover speed transition from Idle to Operating Mode must be ≤ 15 dB.<br>• Startup behavior<br>○ Report Startup behavior re. AC0159<br>○ Startup must proceed smoothly, that is, no sudden or large jumps, and fan speed during startup must not exceed 50% of its maximum<br>• Transient inputs: Report time-history sound pressure levels re AC0159 "Train of Step Functions on Processor" | | | N/A |
| Any | Other | • No rattles, squeaks, or unexpected noises<br>• Sound should be "even" around the EUT (one side should not be dramatically louder than another).<br>• Unless otherwise specified, the "default" thermal-related settings shall be selected for BIOS and iDRAC.<br>• Specific operating conditions are defined in "Configurations and Configuration Dependencies" for each platform. | | | |
| Sound Pressure | LpA-reported, dBA, re AC0158 and program configuration document | Report for all mics | Report for all mics | Report for all mics | Report for all mics |

## Category 3: General Use Space

When Dell determines that a specific Enterprise product is to be predominantly used in a general use space, then the acoustical specification of the table below applies. These products could be found in laboratories, schools, restaurants, open office space layouts, small ventilated closets, etc., though not in close proximity to any particular person nor in quantities greater than a few in any location. People within proximity of a few of these products should not experience any impact to speech intelligibility or annoyance from the noise of the product. A rack product sitting on a table in a common area is an example.

**Table 21. Dell Enterprise Category 3, "General Use" acoustical specification category**

| Measurement Position re AC0158 | Metric, re AC0159 | Test Modes, re AC0159 (note must be in steady state, see AC0159, except where noted below) | | | |
|---|---|---|---|---|---|
| | | Standby in 23±2° C Ambient | Idle in 23±2° C Ambient | Operating in 23±2° C Ambient – if not otherwise specified in the program's configuration document, then processor and hard drive operating modes are required | Simulate (that is, set air mover speeds representative) for Idle at 28° C & 35° C Ambient and for 100% loading and maximum configuration, at 35° C Ambient |
| Sound Power | LwA-m, bels | ≤ 5.2 | ≤ 5.5 | ≤ 5.8 | Report |
| Sound Quality (both positions must meet limits): Front Binaural HEAD and Rear Microphone | Tones, Hz, dB | No prominent tones per criteria D.10.6 and D.10.8 of ECMA-74 | | | Report tones |
| | Tonality, tu | ≤ 0.35 | ≤ 0.35 | ≤ 0.35 | Report |
| | Dell Modulation, % | ≤ 40 | ≤ 40 | ≤ 40 | Report |
| | Loudness, sones | Report | Report | Report | Report |
| | LpA-single point, dBA | Report | Report | Report | Report |
| Front Binaural HEAD | Transients | • Oscillation (see AC0159), if observed, during 20-minute steady-state observation, must adhere to the following two criteria:<br>○ Max. {ΔLpA} < 3.0 dB<br>○ Event count < 3 for "1.5 dB < ΔLpA < 3.0 dB"<br>• Report Acoustical Jump (see AC0159) during air mover speed transition from Idle to Operating Mode.<br>• Startup behavior<br>○ Report Startup behavior re. AC0159<br>○ Startup must proceed smoothly, that is, no sudden or large jumps, and air mover speed during startup must not exceed 50% of its maximum.<br>• Transient inputs: Report time-history sound pressure levels re AC0159 "Train of Step Functions on Processor" | | | N/A |
| Any | Other | No rattles, squeaks, or unexpected noises<br>Sound should be "even" around the EUT (one side should not be dramatically louder than another)<br>Unless otherwise specified, the "default" thermal-related settings shall be selected for BIOS and iDRAC. | | | |

**Table 21. Dell Enterprise Category 3, "General Use" acoustical specification category (continued)**

| Measurement Position re AC0158 | Metric, re AC0159 | Test Modes, re AC0159 (note must be in steady state, see AC0159, except where noted below) | | | |
|---|---|---|---|---|---|
| | | Standby in 23±2° C Ambient | Idle in 23±2° C Ambient | Operating in 23±2° C Ambient – if not otherwise specified in the program's configuration document, then processor and hard drive operating modes are required | Simulate (that is, set air mover speeds representative) for Idle at 28° C & 35° C Ambient and for 100% loading and maximum configuration, at 35° C Ambient |
| | | Specific operating conditions will be defined in "Configurations & Configuration Dependencies" for each platform. | | | |
| Sound Pressure | LpA-reported, dBA, re AC0158 and program configuration document | Report for all mics | Report for all mics | Report for all mics | Report for all mics |

## Category 4: Attended Data Center

When Dell determines that a specific Enterprise product is to be predominantly used in an attended data center, then the acoustical specification of the table applies. The phrase "attended data center" is used to mean a space in which many (from tens to 1000s) of Enterprise products are deployed in proximity (that is, in the same room) to personnel whose speech (perhaps with raised voices) is expected to be intelligible over the data center noise. Hearing protection or hearing monitoring programs are not expected in these areas. Examples in this category include monolithic rack products.

**Table 22. Dell Enterprise Category 4, "Attended Data Center" acoustical specification category.**

| Measurement Position re AC0158 | Metric, re AC0159 | Test Modes, re AC0159 (note must be in steady state, see AC0159, except where noted below) | | | | Simulate (that is, set fan speeds representative) for 100% loading and maximum configuration, at 35° C Ambient |
|---|---|---|---|---|---|---|
| | | Standby in 23±2° C Ambient | Idle in 23±2° C Ambient | Operating in 23±2° C Ambient – if not otherwise specified in the program's configuration document, then processor and hard drive operating modes are required | Simulate (that is, set fan speeds representative) for Idle at 28° C & 35° C Ambient | |
| Sound Power | LwA-m, B | Report | ≤ 6.9 | ≤ 7.1 | Report | ≤ 8.2 |
| Front Binaural HEAD | Tones, Hz, dB | Report | < 15 dB | < 15 dB | Report | < 20 dB |
| | Tonality, tu | Report | Report | Report | Report | Report |
| | Dell Modulation, % | Report | Report | Report | Report | Report |
| | Loudness, sones | Report | Report | Report | Report | Report |
| | LpA-single point, dBA | Report | Report | Report | Report | Report |

**Table 22. Dell Enterprise Category 4, "Attended Data Center" acoustical specification category. (continued)**

| Measurement Position re AC0158 | Metric, re AC0159 | Test Modes, re AC0159 (note must be in steady state, see AC0159, except where noted below) | | | | Simulate (that is, set fan speeds representative ) for 100% loading and maximum configuration, at 35° C Ambient |
|---|---|---|---|---|---|---|
| | | Standby in 23±2° C Ambient | Idle in 23±2° C Ambient | Operating in 23±2° C Ambient – if not otherwise specified in the program's configuration document, then processor and hard drive operating modes are required | Simulate (that is, set fan speeds representative ) for Idle at 28° C & 35° C Ambient | |
| | Transients | • Oscillation (see AC0159), if observed, during 20-minute steady-state observation, must adhere to the following two criteria:<br>○ Max. {ΔLpA} < 3.0 dB<br>○ Event count < 3 for "1.5 dB < ΔLpA < 3.0 dB"<br>○ Acoustical Jump (see AC0159), during air mover speed transition from Idle to Operating Mode must be ≤ 15 dB.<br>○ Startup behavior<br>▪ Report Startup behavior re. AC0159<br>▪ Startup must proceed smoothly, that is, no sudden or large jumps, and fan speed during startup must not exceed 50% of its maximum<br>∞ Transient inputs: Report time-history sound pressure levels re AC0159 "Train of Step Functions on Processor" | | | | N/A | |
| Any | Other | No rattles, squeaks, or unexpected noises<br>Sound should be "even" around the EUT (one side should not be dramatically louder than another)<br>Unless otherwise specified, the "default" thermal-related settings shall be selected for BIOS and iDRAC.<br>Specific operating conditions will be defined in "Configurations & Configuration Dependencies" for each platform. | | | | |
| Sound Pressure | LpA-reported, dBA | Report for all mics | Report for all mics | Report for all mics | Report for all mics | Report for all mics |

## Category 5: Unattended Data Center

When Dell determines that a specific Enterprise product is to be predominantly used in an unattended data center (and not blades or blade enclosures; these have their own category), then the acoustical specification in the table below applies. The phrase "unattended data center" is used to mean a space in which many (from tens to 1000s) of Enterprise products are deployed together, its own heating and cooling systems condition the space, and operators or servicers of equipment enter generally only to deploy, service, or decommission equipment. Hearing protection or hearing monitoring programs may be expected (per government or company guidelines) in these areas. Examples in this category include monolithic rack products.

### Table 23. Dell Enterprise Category 5, "Unattended Data Center" acoustical specification category

| Measurement Position re AC0158 | Metric, re AC0159 | Test Modes, re AC0159 (note must be in steady state, see AC0159, except where noted below) | | | | Simulate (that is, set air mover speeds representative) for 100% loading and maximum configuration, at 35° C Ambient |
|---|---|---|---|---|---|---|
| | | Standby in 23±2° C Ambient | Idle in 23±2° C Ambient | Operating in 23±2° C Ambient – if not otherwise specified in the program's configuration document, then processor and hard drive operating modes are required | Simulate (that is, set air mover speeds representative) for Idle at 28° C & 35° C Ambient | |
| Sound Power | LwA-m, bels | Report | ≤ 7.5 | ≤ 7.7 | Report | ≤ 8.7 |
| Front Binaural HEAD | Tones, Hz, dB | Report | < 15 dB | < 15 dB | Report | < 20 dB |
| | Tonality, tu | Report | Report | Report | Report | Report |
| | Dell Modulation, % | Report | Report | Report | Report | Report |
| | Loudness, sones | Report | Report | Report | Report | Report |
| | LpA-single point, dBA | Report | Report | Report | Report | Report |
| Front Binaural HEAD | Transients | • Oscillation (see AC0159), if observed, during 20-minute steady-state observation, must adhere to the following two criteria:<br>○ Max. {ΔLpA} < 3.0 dB<br>○ Event count < 3 for "1.5 dB < ΔLpA < 3.0 dB"<br>• Report Acoustical Jump (see AC0159) during air mover speed transition from Idle to Operating Mode.<br>• Startup behavior<br>○ Report Startup behavior re. AC0159<br>○ Startup must proceed smoothly, that is, no sudden or large jumps, and air mover speed during startup must not exceed 50% of its maximum<br>• Transient inputs: Report time-history sound pressure levels re AC0159 "Train of Step Functions on Processor" | | | N/A | |
| Any | Other | No rattles, squeaks, or unexpected noises<br>Sound should be "even" around the EUT (one side should not be dramatically louder than another)<br>Unless otherwise specified, the "default" thermal-related settings shall be selected for BIOS and iDRAC.<br>Specific operating conditions will be defined in "Configurations & Configuration Dependencies" for each platform. | | | | |

**Table 23. Dell Enterprise Category 5, "Unattended Data Center" acoustical specification category (continued)**

| Measurement Position re AC0158 | Metric, re AC0159 | Test Modes, re AC0159 (note must be in steady state, see AC0159, except where noted below) | | | | Simulate (that is, set air mover speeds representative) for 100% loading and maximum configuration, at 35° C Ambient |
|---|---|---|---|---|---|---|
| | | Standby in 23±2° C Ambient | Idle in 23±2° C Ambient | Operating in 23±2° C Ambient – if not otherwise specified in the program's configuration document, then processor and hard drive operating modes are required | Simulate (that is, set air mover speeds representative) for Idle at 28° C & 35° C Ambient | |
| Sound Pressure | LpA-reported, dBA, re AC0158 and program configuration document | Report for all mics | Report for all mics | Report for all mics | Report for all mics | Report for all mics |

# Acoustical configurations of T360

Dell PowerEdge T360 is a tower server appropriate for typical office environments.

**Table 24. Configurations tested for acoustical experience**

| Configuration | Quietest Config | Entry | Volume | Feature Rich with GPU | Feature Rich Max. Storage |
|---|---|---|---|---|---|
| Processor | Raptor Lake, 65 W | Raptor Lake, 65 W | Raptor Lake, 65 W | Raptor Lake, 95 W | Raptor Lake, 95 W |
| Processor Quantity | 1 | 1 | 1 | 1 | 1 |
| Memory | 16 GB UDIMM | 16 GB UDIMM | 16 GB UDIMM | 32 GB UDIMM | 32 GB UDIMM |
| Memory Quantity | 1 | 1 | 2 | 4 | 4 |
| Storage | 3.5" SATA 2-TB HDD | 3.5" SATA 2-TB HDD | 3.5" SATA 2-TB HDDs | 3.5" SATA 2-TB HDDs | 2.5" SAS 600 GB |
| Storage Quantity | 1 | 1 | 2 | 4 | 8 |
| Backplane | 4x 3.5" hot swap | 4x 3.5" hot swap | 8x 3.5" hot swap | 8x 3.5" hot swap | 8x 3.5" hot swap |
| Power Supply Unit | 450 W (106 mm) | 450 W (106 mm) | 600 W (60 mm) | 600 W (60 mm) | 600 W (60 mm) |
| Power Supply Quantity | 1 | 1 | 2 | 2 | 2 |
| PCIe Cards | PERC H355 | PERC H355 | PERC H355 | PERC H755 2x 1 GbE NIC A2 GPU (60 W) | PERC H755 2x 1 GbE NIC |
| Bezel | N/A | N/A | Yes | Yes | Yes |
| Other | N/A | N/A | ODD | ODD | ODD |

### Table 25. Acoustical performance of T360 acoustical configurations

| Configuration | | Quietest Config | Entry | Volume | Feature Rich with GPU | Feature Rich Max. Storage |
|---|---|---|---|---|---|---|
| Acoustical Performance: Idle/ Operating @ 25 °C Ambient | | | | | | |
| $L_{wA,m}$ (B) | Idle | 3.6 | 3.6 | 3.8 | 5.4 | 3.5 |
| | Operating | 3.8 | 3.8 | 3.8 | 7.5 | 4.7 |
| $K_v$ (B) | Idle | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 |
| | Operating | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 |
| $L_{pA,m}$ (dB) | Idle | 24 | 24 | 27 | 41 | 28 |
| | Operating | 27 | 27 | 28 | 63 | 37 |
| Prominent tones | | No prominent tones in Idle and Operating | | | | |
| Acoustical Performance: Idle @ 28 °C Ambient | | | | | | |
| $L_{wA,m}$ (B) | | 3.6 | 3.6 | 3.8 | 5.4 | 3.5 |
| $K_v$ (B) | | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 |
| $L_{pA,m}$ (dB) | | 24 | 24 | 27 | 41 | 28 |
| Acoustical Performance: Max. Loading @ 35 °C Ambient | | | | | | |
| $L_{wA,m}$ (B) | | 7.1 | 7.1 | 7.2 | 7.5 | 7.2 |
| $K_v$ (B) | | 0.4 | 0.4 | 0.4 | 0.4 | 0.4 |
| $L_{pA,m}$ (dB) | | 61 | 61 | 61 | 63 | 61 |

(1)LwA,m: The declared mean A-weighted sound power level (LwA) is calculated per section 5.2 of ISO 9296 (2017) with data collected using the methods that are described in ISO 7779 (2010). Data presented here may not be fully compliant with ISO 7779 declaration requirement.

(2)LpA,m: The declared mean A-weighted emission sound pressure level is at the bystander position per section 5.3 of ISO 9296 (2017) and measured using methods that are described in ISO 7779 (2010). The system is placed on a standard table, 75 cm above a reflective floor. Data presented here may not be fully compliant with ISO 7779 declaration requirement.

(3)Prominent tones: Criteria of D.6 and D.11 of ECMA-74 (17th ed., Dec. 2019) are followed to determine if discrete tones are prominent and to report them, if so.

(4)Idle mode: The steady-state condition in which the server is energized but not operating any intended function.

(5)Operating mode: The maximum of the steady state acoustical output at 50% of CPU TDP or active storage drives per C.9.3.2 in ECMA-74 (17th ed., Dec. 2019).

## Power Capping

The PowerEdge T360 supports the NVIDIA A2 GPU, which provides enterprise-level performance, therefore, louder acoustic performance is expected. Power capping solutions provides better acoustic performance by limiting GPU performance by up to 20%.

### Table 26. Acoustical performance of T360 on power capping

| T360 | Without Power Capping | With Power Capping |
|---|---|---|
| Acoustic Performance | 7.5 bels | 5.9 bels |
| Category | Category 5 | Category 4 |

**NOTE:** PowerEdge T360 with GPU workload is not recommend for an acoustically sensitive environment.

# 10

# Operating Systems and Virtualization

**Topics:**

- Supported Operating Systems

## Supported Operating Systems

The PowerEdge system supports the following operating systems:

- Canonical® Ubuntu® Server LTS
- Microsoft® Windows Server® with Hyper-V
- Red Hat® Enterprise Linux
- SUSE® Linux Enterprise server
- VMware® ESXi®

Links to specific OS versions and editions, certification matrices, Hardware Compatibility Lists (HCL) portal, and Hypervisor support are available at Dell Enterprise Operating Systems.

# 11

# Dell OpenManage Systems Management

Dell delivers management solutions that help IT administrators effectively deploy, update, monitor, and manage IT assets. OpenManage solutions and tools enable you to quickly respond to problems by helping them to manage Dell servers efficiently; in physical, virtual, local, and remote environments; all without the need to install an agent in the operating system.

The OpenManage portfolio includes:

- Innovative embedded management tools - integrated Dell Remote Access Controller (iDRAC)
- Consoles - OpenManage Enterprise
- Extensible with plug-ins - OpenManage Power Manager
- Update tools - Repository Manager

Dell has developed comprehensive systems management solutions that are based on open standards and has integrated with management consoles from partners such as Microsoft and VMware, allowing advanced management of Dell servers. Dell management capabilities extend to offerings from the industry's top systems management vendors and frameworks such as Ansible, Splunk, and ServiceNow. OpenManage tools automate the full span of server life cycle management activities along with powerful RESTful APIs to script or integrate with your choice of frameworks.

For more information about the entire OpenManage portfolio, see:

- The latest Dell Systems Management Overview Guide.

**Topics:**


- Integrated Dell Remote Access Controller (iDRAC)
- Systems Management software support matrix


# Integrated Dell Remote Access Controller (iDRAC)

iDRAC9 delivers advanced, agent-free, local and remote server administration. Embedded in every PowerEdge server, iDRAC9 provides a secure means to automate a multitude of common management tasks. Because iDRAC is embedded within every PowerEdge server, there is no additional software to install; just plug in power and network cables, and iDRAC is ready to go. Even before installing an operating system (operating system) or hypervisor, IT administrators have a complete set of server management features at their fingertips.

With iDRAC9 in-place across the Dell PowerEdge portfolio, the same IT administration techniques and tools can be applied throughout. This consistent management platform allows easy scaling of PowerEdge servers as an organization's infrastructure grows. Customers can use the iDRAC RESTful API for the latest in scalable administration methods of PowerEdge servers. With this API, iDRAC enables support for the Redfish standard and enhances it with Dell extensions to optimize at-scale management of PowerEdge servers. By having iDRAC at the core, the entire OpenManage portfolio of Systems Management tools allows every customer to tailor an effective, affordable solution for any size environment.

Zero Touch Provisioning (ZTP) is embedded in iDRAC. ZTP - Zero Touch Provisioning is Intelligent Automation Dell's agent-free management puts IT administrators in control. Once a PowerEdge server is connected to power and networking, that system can be monitored and fully managed, whether you're standing in front of the server or remotely over a network. In fact, with no need for software agents, an IT administrator can: · Monitor · Manage · Update · Troubleshoot and remediate Dell servers With features like zero-touch deployment and provisioning, iDRAC Group Manager, and System Lockdown, iDRAC9 is purpose-built to make server administration quick and easy. For those customers whose existing management platform utilizes in-band management, Dell does provide iDRAC Service Module, a lightweight service that can interact with both iDRAC9 and the host operating system to support legacy management platforms.

When ordered with DHCP enabled from the factory, PowerEdge servers can be automatically configured when they are initially powered up and connected to your network. This process uses profile-based configurations that ensure each server is configured per your specifications. This feature requires an iDRAC Enterprise license.

iDRAC9 offers following license tiers:

### Table 27. iDRAC9 license tiers

| License | Description |
|---|---|
| iDRAC9 Basic | • Available only on 100-500 series rack/tower<br>• Basic instrumentation with iDRAC web UI<br>• For cost conscious customers that see limited value in management |
| iDRAC9 Express | • Default on 600+ series rack/tower, modular, and XR series<br>• Includes all features of Basic<br>• Expanded remote management and server life-cycle features |
| iDRAC9 Enterprise | • Available as an upsell on all servers<br>• Includes all features of Basic and Express. Includes key features such as virtual console, AD/LDAP support, and more<br>• Remote presence features with advanced, Enterprise-class, management capabilities |
| iDRAC9 Datacenter | • Available as an upsell on all servers<br>• Includes all features of Basic, Express, and Enterprise. Includes key features such as telemetry streaming, Thermal Manage, automated certificate management, and more<br>• Extended remote insight into server details, focused on high end server options, granular power, and thermal management |

For a full list of iDRAC features by license tier, see Integrated Dell Remote Access Controller 9 User's Guide at Dell.com.

For more details on iDRAC9 including white papers and videos, see:

- Support for Integrated Dell Remote Access Controller 9 (iDRAC9) on the Knowledge Base page at Dell.com

# Systems Management software support matrix

### Table 28. Systems Management software support matrix

| Categories | Features | PE mainstream |
|---|---|---|
| Embedded Management and In-band Services | iDRAC9 (Express, Enterprise, and Datacenter licenses) | Supported |
| | OpenManage Mobile | Supported |
| | OM Server Administrator (OMSA) | Supported |
| | iDRAC Service Module (iSM) | Supported |
| | Driver Pack | Supported |
| Change Management | Update Tools (Repository Manager, DSU, Catalogs) | Supported |
| | Server Update Utility | Supported |
| | Lifecycle Controller Driver Pack | Supported |
| | Bootable ISO | Supported |
| Console and Plug-ins | OpenManage Enterprise | Supported |
| | Power Manager Plug-in | Supported |
| | Update Manager Plug-in | Supported |
| | SupportAssist Plug-in | Supported |
| | CloudIQ | Supported |
| Integrations and connections | OM Integration with VMware Vcenter/vROps | Supported |
| | OM Integration with Microsoft System Center (OMIMSC) | Supported |
| | Integrations with Microsoft System Center and Windows Admin Center (WAC) | Supported |

**Table 28. Systems Management software support matrix (continued)**

| Categories | Features | PE mainstream |
|---|---|---|
| | ServiceNow | Supported |
| | Ansible | Supported |
| | Third-party Connectors (Nagios, Tivoli, Microfocus) | Supported |
| Security | Secure Enterprise Key Management | Supported |
| | Secure Component Verification | Supported |
| Standard operating system | Red Hat Enterprise Linux, SUSE, Windows Server 2019 or 2022, Ubuntu, CentOS | Supported (Tier-1) |

12

# Appendix D: Service and support

**Topics:**


- Default support levels
- Other services and support information


# Default support levels

This system offers 3 years Dell ProSupport Next Business Day (NBD), including 24x7 phone support and NBD parts and labor support.

## Default deployment levels

This system is defaulted to the ProDeploy Dell Server which includes onsite hardware installation and remote software configuration. Optionally, the customer may choose to any of the factory or field deployment offers listed below.

# Other services and support information

Dell Technologies Services include a wide, customizable range of service options to simplify the assessment, design, implementation, management and maintenance of IT environments and to help transition from platform to platform.

Depending on the current business requirements and correct level of service for customers, we provide factory, onsite, remote, modular, and specialized services that fit the customer requirements and budget. We will help with a little or a lot, based on the customers choice, and provide access to our global resources.

## Dell deployment services

### Dell ProDeploy Infrastructure Suite

ProDeploy Infrastructure Suite provides a variety of deployment offerings that satisfy a customer's unique needs. It is made up of 5 offers: ProDeploy Configuration Services, ProDeploy Rack Integration Services, Basic Deployment, ProDeploy, and ProDeploy Plus.





**Figure 10. ProDeploy Infrastructure Suite for servers**

The new Factory Services consist of two tiers of deployment that happen prior to shipping to the customer's site.

**Factory Based Services:**

- ProDeploy Factory Configuration - Ideal for customers buying servers in volume and seeking pre-configuration prior to shipping such as: custom image, system settings, and asset tagging so it arrives ready to use out of the box. Furthermore, servers can be packaged and bundled to meet specific shipping and distribution requirements for each customer location to facilitate the rollout process. Upsell one of the field based services (below) if a customer needs assistance with the final server installation.
- ProDeploy Rack Integration - Ideal for customers seeking to build out fully integrated racks prior to shipping. These rack builds include hardware install, cabling, and full system configuration. You can also add-on a factory stress test and optional on-site final rack configuration to complete the rack installation.
  - STANDARD SKUs for Rack Integration is available in US only and requires:
    - 20 or more devices (R and C series servers and all Dell or non-Dell switches). Use Informational SKUs for Dell switches or 3rd party products
    - Shipping to contiguous US
  - USE CUSTOM QUOTE for Rack Integration for:
    - All countries except USA
    - Racks containing less than 20 servers
    - Any rack that includes VxRail or Storage
    - Shipping outside contiguous US
    - Shipping to multiple locations

**Field Based Services:**

- Basic Deployment consists of the hardware installation, cabling and firmware update during normal standard business hours. Basic Deployment is traditionally sold to Competency Enabled Partners. Competency enabled partners often have Dell do the hardware installation while they complete the software configuration.
- ProDeploy consists of your hardware installation and configuration of the software using offshore resources. ProDeploy is great for customers who are price sensitive or who are remote from their data centers and don't require an onsite presence.
- ProDeploy Plus will give you in-region or onsite resources to complete the engagement for the customer. It also comes with additional features such as Post Deployment Configuration Assistance and Training Credits.





**Figure 11. ProDeploy Infrastructure Suite - Factory services**





**Figure 12. ProDeploy Infrastructure Suite - Field services**

## Dell ProDeploy Plus for Infrastructure

From beginning to end, ProDeploy Plus provides the skill and scale that is must successfully perform demanding deployments in today's complex IT environments. Certified Dell experts start with extensive environmental assessments and detailed migration

planning and recommendations. Software installation includes set up of our enterprise connectivity solution (secure connect gateway) and OpenManage system management utilities.

Postdeployment configuration assistance, testing, and product orientation services are also available.

## Dell ProDeploy for Infrastructure

ProDeploy provides full-service installation and configuration of both server hardware and system software by certified deployment engineers including set up of leading operating systems and hypervisors as well our enterprise connectivity solution (secure connect gateway) and OpenManage system management utilities. To prepare for the deployment, we conduct a site readiness review and implementation planning exercise. System testing, validation, and full project documentation with knowledge transfer complete the process.

## Dell Basic Deployment

Basic Deployment delivers worry-free professional installation by experienced technicians who know Dell servers inside and out.

## Additional Deployment Services

You can tailor the ProDeploy Infrastructure Suite offer to meet your customer's unique needs by leveraging "Additional Deployment Time." ADT will cover additional tasks above the normal scope of the standard offers. ADT can be sold for Project Management or Technical Resources and is sold as blocks of four hours remote or eight hours on-site.

## Dell ProDeploy for HPC (available in US/Canada only. All other regions use custom)

HPC deployments require specialists that understand that cutting edge is yesterday's news. Dell deploys the world 's fastest systems and understands the nuances that make them perform. ProDeploy for HPC provides:

- Global team of dedicated HPC specialists
- Proven track record, thousands of successful HPC deployments
- Design validation, benchmarking, and product orientation

Learn more at Dell.com/HPC-Services.





**Figure 13. ProDeploy Expansion for HPC**

## Dell custom deployment Services

Dell custom rack integration and other Dell configuration services help customers save time by providing systems that are racked, cabled, tested, and ready to be integrated into the data center. Dell support preconfigure RAID, BIOS and iDRAC settings, install system images, and even install third-party hardware and software.

For more information, see Server Configuration Services.

## Dell Residency Services

Residency Services help customers transition to new capabilities quickly with the assistance of onsite or remote Dell experts whose priorities and time they control.

Residency experts can provide post implementation management and knowledge transfer that is related to a new technology acquisition or day-to-day operational management of the IT infrastructure.

## Dell Data Migration Services

Protect business and data of the customer with our single point of contact to manage data migration projects.

A customer project manager works with our experienced team of experts to create a plan using industry-leading tools and proven processes that are based on global best practices to migrate existing files and data, so business systems are up and running quickly and smoothly.

# Dell Enterprise Support Services

## Dell ProSupport Enterprise Suite

With the ProSupport Enterprise Suite, we help keep IT systems running smoothly, so customers can focus on running their business. We help maintain peak performance and availability of the most essential workloads. ProSupport Enterprise Suite is a suite of support services that enable customers to build the solution that is right for their organization. They choose support models that are based on how they use technology and where they want to allocate resources. From the desktop to the data center, address everyday IT challenges, such as unplanned downtime, mission-critical needs, data and asset protection, support planning, resource allocation, software application management and more. Optimize customer IT resources by choosing the right support model.

**Table 29. ProSupport Enterprise Suite**

| Service | Support model | Description |
|---|---|---|
| ProSupport Enterprise Suite | ProSupport Plus for Enterprise | Proactive, predictive, and reactive support for systems that look after your business-critical applications and workloads |
| | ProSupport for Enterprise | Comprehensive 24 x 7 predictive and reactive support for hardware and software |
| | Basic hardware support | Reactive hardware support during normal business hours |

## Dell ProSupport Plus for Enterprise

When customers purchase PowerEdge server, we recommend ProSupport Plus, our proactive and preventative support service for business-critical systems. ProSupport Plus provides all the benefits of ProSupport, plus the following:

- An assigned Services Account Manager who knows their business and environment
- Immediate advanced troubleshooting from an engineer
- Personalized, preventive recommendations that are based on analysis of support trends and best practices from across the Dell Technologies infrastructure solutions customer base to reduce support issues and improve performance
- Predictive analysis for issue prevention and optimization that is enabled by secure connect gateway technology
- Proactive monitoring, issue detection, notification, and automated case creation for accelerated issue resolution enabled by secure connect gateway
- On-demand reporting and analytics-based recommendations that are enabled by secure connect gateway and TechDirect

## Dell ProSupport for Enterprise

ProSupport service offers highly trained experts around the clock and around the globe to address IT needs. We help minimize disruptions and maximize availability of PowerEdge server workloads with:

- 24x7 support through phone, chat and online
- Predictive, automated tools and innovative technology
- A central point of accountability for all hardware and software issues
- Collaborative third-party support
- Hypervisor, operating system and application support
- Consistent experience regardless of where customers are located or what language they speak

  **NOTE:** Subject to service offer country or region availability.
- Optional onsite parts and labor response options including next business day or four-hour mission critical





**Figure 14. ProSupport Enterprise Suite**

## Dell ProSupport One for Data Center

ProSupport One for Data Center offers flexible site-wide support for large and distributed data centers with more than 1,000 assets. This offering is built on standard ProSupport components that leverage our global scale but are tailored to a customer's needs. While not for everyone, this service option offers a truly unique solution for Dell Technologies largest customers with the most complex environments.

- Team of assigned Services Account Managers with remote, on-site options
- Assigned ProSupport One technical and field engineers who are trained on the customer's environment and configurations
- On-demand reporting and analytics-based recommendations that are enabled by secure connect gateway and TechDirect
- Flexible on-site support and parts options that fit their operational model
- A tailored support plan and training for their operations staff

## Dell ProSupport Add-on for HPC

The ProSupport Add-on for HPC provides solution-aware support including:

- Access to senior HPC experts
- Advanced HPC cluster assistance: performance, interoperability, and configuration
- Enhanced HPC solution level end-to-end support
- Remote presupport engagement with HPC Specialists during ProDeploy implementation

Learn more at Dell.com/HPC-Services.





**Figure 15. ProSupport Add-on for HPC is an add-on to PS or PSP**

## Support Technologies

Powering the support experience with predictive, data-driven technologies.

**NOTE:** SupportAssist Enterprise capabilities are now part of the secure connect gateway technology.

# Enterprise connectivity

The best time to solve a problem is before it happens. The automated proactive and predictive support features enabled by the secure connect gateway technology helps reduce steps and time to resolution, often detecting issues before they become a crisis. The gateway technology is available in virtual and application editions. It is also implemented as a direct connect version for select Dell hardware and a Services plugin within OpenManage Enterprise for PowerEdge servers. The legacy SupportAssist Enterprise solution has been retired and is now replaced by the secure connect gateway solutions.

Benefits include:

- Value: Our connectivity solutions are available to all customers at no additional charge
- Improve productivity: Replace manual, high-effort routines with automated support
- Accelerate time to resolution: Receive issue alerts, automatic case creation, and proactive contact from Dell experts
- Gain insight and control: Optimize enterprise devices with insights in portals reporting like TechDirect, and get predictive issue detection before the problem starts

**NOTE:** Connect devices can access these features. Features vary depending on the service level agreement for the connected device. ProSupport Plus customers experience the full set of automated support capabilities.

**Table 30. Features enabled by connectivity**

| — | Basic hardware warranty | ProSupport | ProSupport Plus |
|---|---|---|---|
| Automated issue detection and system state information collection | Supported | Supported | Supported |
| Proactive, automated case creation and notification | Not supported | Supported | Supported |

**Table 30. Features enabled by connectivity (continued)**

| — | Basic hardware warranty | ProSupport | ProSupport Plus |
|---|---|---|---|
| Predictive issue detection for failure prevention | Not supported | Not supported | Supported |

Get started at DellTechnologies.com/secureconnectgateway.

# Dell TechDirect

TechDirect helps boost IT team productivity when supporting Dell systems.

Boost your productivity with online servoce for Dell products from TechDirect. From deployment to technical support, TechDirect lets you do more with less effort and faster resolution. You can:

- OPen and manage support requests or in-warranty systems
- Execute online self-service for parts dispatch
- Collaborate on ProDeploy infrastructure deployment projects online
- Manage proactive and preditive alerts from secure connect gateway technology that help maximize uptime
- Integrate services functionality into your help desk with TechDirect APIs
- Join over 10,000 companies that choose TechDirect

Register at TechDirect.Dell.com.

# Dell Technologies Consulting Services

Our expert consultants help customers transform faster, and quickly achieve business outcomes for the high value workloads Dell PowerEdge systems can handle. From strategy to full-scale implementation, Dell Technologies Consulting can help determine how to perform IT, workforce, or application transformation. We use prescriptive approaches and proven methodologies that are combined with portfolio and partner ecosystem of Dell Technologies to help achieve real business outcomes. From multi cloud, applications, DevOps, and infrastructure transformations, to business resiliency, data center modernization, analytics, workforce collaboration, and user experiences-we are here to help.

## Dell Managed Services

Some customers prefer Dell to manage the complexity and risk of daily IT operations, Dell Managed Services utilizes proactive, AI enabled delivery operations and modern automation to help customers realize desired business outcomes from their infrastructure investments. With these technologies, our experts run, update and fine-tune customer environments aligned with service levels, while providing environment-wide and down-to-the-device visibility. There are two types of managed service offers. First the outsourcing model or CAPEX model where Dell manages the customer owned assets using our people and tools. The second is the as-a-Service model or OPEX model called APEX. In this service, Dell owns all technology and all the management of it. Many customers will have a blend of the two management types depending on the goals of the organization.




**Figure 16. Dell Managed Services**

## Dell Technologies Education Services

Build the IT skills required to influence the transformational outcomes of the business. Enable talent and empower teams with the right skills to lead and perform transformational strategy that drives competitive advantage. Leverage the training and certification required for real transformation.

Dell Technologies Education Services offers PowerEdge server training and certifications that are designed to help customers achieve more from their hardware investment. The curriculum delivers the information and the practical, firsthand skills that their team must confidently install, configure, manage, and troubleshoot Dell servers.

To learn more or register for a class today, see Education.Dell.com.

13

# Appendix A: Additional specifications

**Topics:**


- Chassis dimensions
- System weight
- NIC port specifications
- Video specifications
- USB Ports
- PSU rating
- Environmental specifications


## Chassis dimensions





**Figure 17. Chassis dimensions**

**Table 31. Chassis dimension for the system**

| Drives | Xa | Xb | Ya | Yb | Yc | Za (with bezel) | Za (without bezel) | Zb | Zc |
|---|---|---|---|---|---|---|---|---|---|
| 8 x 3.5-inch SAS/SATA HDD/SSD | 175.0 mm (6.89 inches) | N/A | 369.5 mm (14.55 inches) | 382.5 mm (15.06 inches) | N/A | 19 mm (0.75 inches) | N/A | 560.5 mm (22.07 inches) | 562.12 mm (22.13 inches) |

# System weight

### Table 32. PowerEdge T360 system weight

| System configuration | Maximum weight (with all drives/SSDs) |
|---|---|
| A server with fully populated drives | 25.10 kg (55.34 lbs) |
| A server without drives and PSU installed | 18.29 kg (40.32 lbs) |

# NIC port specifications

The PowerEdge T360 system supports up to two 10/100/1000 Mbps Network Interface Controller (NIC) ports embedded on the LAN on Motherboard (LOM).

### Table 33. NIC port specification for the system

| Feature | Specifications |
|---|---|
| LOM on Planar | 2 x 1 GbE |
| Network Card | 1 GbE x 4, 10 GbE x 2, 10 GbE x 4 |

# Video specifications

The PowerEdge T360 system supports integrated Matrox G200eW graphics controller with 16 MB of video frame buffer.

### Table 34. Supported video resolution options

| Resolution | Refresh rate (Hz) | Color depth (bits) |
|---|---|---|
| 640 x 480 | 60 Hz | 32 |
| 640 x 480 | 72 Hz | 32 |
| 640 x 480 | 75 Hz | 32 |
| 640 x 480 | 85 Hz | 32 |
| 800 x 600 | 60 Hz | 32 |
| 800 x 600 | 72 Hz | 32 |
| 800 x 600 | 75 Hz | 32 |
| 800 x 600 | 85 Hz | 32 |
| 1024 x 768 | 60 Hz | 32 |
| 1024 x 768 | 72 Hz | 32 |
| 1024 x 768 | 75 Hz | 32 |
| 1024 x 768 | 85 Hz | 32 |
| 1280 x 800 | 60 Hz | 32 |
| 1280 x 800 | 75 Hz | 32 |
| 1280 x 1024 | 60 Hz | 32 |
| 1280 x 1024 | 75 Hz | 32 |
| 1360 x 768 | 60 Hz | 32 |
| 1440 x 900 | 60 Hz | 32 |
| 1440 x 900 | 60 Hz (RB) | 32 |

### Table 34. Supported video resolution options (continued)

| Resolution | Refresh rate (Hz) | Color depth (bits) |
|---|---|---|
| 1600 x 900 | 60 Hz (RB) | 32 |
| 1600 x 900 | 60 Hz (RB) | 32 |
| 1600 x 1200 | 60 Hz | 32 |
| 1600 x 1200 | 60 Hz (RB) | 32 |
| 1680 x 1050 | 60 Hz (RB) | 32 |
| 1680 x 1050 | 60 Hz | 32 |
| 1920 x 1080 | 60 Hz | 32 |
| 1920 x 1080 | 60 Hz (RB) | 32 |
| 1920 x 1200 | 60 Hz | 32 |
| 1920 x 1200 | 60 Hz (RB) | 32 |

# USB Ports

### Table 35. PowerEdge T360 USB port specifications

| Front | | Rear | | Internal (Optional) | |
|---|---|---|---|---|---|
| Port type | No. of ports | Port type | No. of ports | Port type | No. of ports |
| USB 2.0 | One | USB 2.0 | Three | USB 3.2 Gen1 | One |
| USB 3.2 Gen1 | One | USB 3.2 Gen1 | Three | | |

# PSU rating

Below table lists the power capacity of the PSUs in high/low line operation mode.

### Table 36. PSUs High line and Low line ratings

| — | 450 W Platinum 106 mm | 600 W Platinum 60 mm | 700 W Titanium 60 mm |
|---|---|---|---|
| AC High Line | 450 W | 600 W | 700 W |
| AC Low Line | 450 W | 600 W | N/A |
| High Line 240 VDC | N/A | 600 W | 700 W |
| High Line 200 - 380 VDC | N/A | N/A | N/A |
| DC -(48 to 60 V) | N/A | N/A | N/A |

The PowerEdge T360 supports up to two AC power supplies with 1+1 redundancy, autosensing, and auto switching capability.

If two PSUs are present during POST, a comparison is made between the wattage capacities of the PSUs. In case the PSU wattages do not match, the larger of the two PSUs is enabled. Also, there is a PSU mismatch warning that is displayed in BIOS, iDRAC, or on the system LCD.

If a second PSU is added at run-time, in order for that particular PSU to be enabled, the wattage capacity of the first PSU must equal the second PSU. Otherwise, the PSU is flagged as unmatched in iDRAC and the second PSU is not enabled.

The PowerEdge T360 also supports a single cabled AC power supply unit.

Dell PSUs have achieved Platinum efficiency levels as shown in the table below.

### Table 37. PSU efficiency level

| Efficiency Targets by Load | | | | | | |
|---|---|---|---|---|---|---|
| **Form factor** | **Output** | **Class @HLAC** | **10%** | **20%** | **50%** | **100%** |
| Redundant 60 mm | 600 W | Platinum | - | 90.00% | 94.00% | 91.00% |
| | 700 W | Titanium | 90.00% | 94.00% | 96.00% | 91.00% |
| Cabled 106 mm | 450 W | Platinum | - | 90.00% | 94.00% | 91.00% |

# Environmental specifications

**NOTE:** For additional information about environmental certifications, refer to the *Product Environmental Datasheet* located with the *Documentation* on support.

### Table 38. Continuous Operation Specifications for ASHRAE A2

| Temperature | Allowable continuous operations |
|---|---|
| Temperature range for altitudes <= 900 m (<= 2953 ft) | 10–35°C (50–95°F) with no direct sunlight on the equipment |
| Humidity percent range (non-condensing at all times) | 8% RH with -12°C minimum dew point to 80% RH with 21°C (69.8°F) maximum dew point |
| Operational altitude de-rating | Maximum temperature is reduced by 1°C/300 m (33.8°F/984 Ft) above 900 m (2953 Ft). |

### Table 39. Continuous Operation Specifications for ASHRAE A3

| Temperature | Allowable continuous operations |
|---|---|
| Temperature range for altitudes <= 900 m (<= 2953 ft) | 5–40°C (41–104°F) with no direct sunlight on the equipment |
| Humidity percent range (non-condensing at all times) | 8% RH with -12°C minimum dew point to 85% RH with 24°C (75.2°F) maximum dew point |
| Operational altitude de-rating | Maximum temperature is reduced by 1°C/175 m (33.8°F/574 Ft) above 900 m (2953 Ft). |

### Table 40. Continuous Operation Specifications for ASHRAE A4

| Temperature | Allowable continuous operations |
|---|---|
| Temperature range for altitudes <= 900 m (<= 2953 ft) | 5–45°C (41–113°F) with no direct sunlight on the equipment |
| Humidity percent range (non-condensing at all times) | 8% RH with -12°C minimum dew point to 90% RH with 24°C (75.2°F) maximum dew point |
| Operational altitude de-rating | Maximum temperature is reduced by 1°C/125 m (33.8°F/410 Ft) above 900 m (2953 Ft). |

### Table 41. Continuous Operation Specifications for Rugged Environment

| Temperature | Allowable continuous operations |
|---|---|
| Temperature range for altitudes <= 900 m (<= 2953 ft) | 5–55°C (41–131°F) with no direct sunlight on the equipment |
| Humidity percent range (non-condensing at all times) | 8% RH with -12°C minimum dew point to 90% RH with 24°C (75.2°F) maximum dew point |
| Operational altitude de-rating | Maximum temperature is reduced by 1°C/125 m (33.8°F/410 Ft) above 900 m (2953 Ft). |

### Table 42. Common Environmental Specifications for ASHRAE A2, A3, A4, and Rugged

| Allowable continuous operations | |
|---|---|
| Maximum temperature gradient (applies to both operation and non-operation). | 20°C in an hour* (36°F in an hour) and 5°C in 15 minutes (41°F in 15 minutes), 5°C in an hour* (41°F in an hour) for tape<br>**NOTE:** * - Per ASHRAE thermal guidelines for tape hardware, these are not instantaneous rates of temperature change. |
| Non-operational temperature limits | -40 to 65°C (-40 to 149°F) |
| Non-operational humidity limits | 5% to 95% RH with 27°C (80.6°F) maximum dew point |
| Maximum non-operational altitude | 12,000 meters (39,370 ft) |
| Maximum operational altitude | 3,048 meters (10,000 ft) |

### Table 43. Maximum vibration specifications

| Maximum vibration | Specifications |
|---|---|
| Operating | 0.26 $G_{rms}$ at 5 Hz to 350 Hz (all operation orientations) |
| Storage | 1.88 $G_{rms}$ at 10 Hz to 500 Hz for 15 minutes (all six sides tested) |

### Table 44. Maximum shock pulse specifications

| Maximum shock pulse | Specifications |
|---|---|
| Operating | Six consecutively executed shock pulses in the positive and negative x, y, and z axis of 6 G for up to 11 ms. |
| Storage | Six consecutively executed shock pulses in the positive and negative x, y, and z axis (one pulse on each side of the system) of 71 G for up to 2 ms. |

## Thermal restriction matrix

### Table 45. Label reference

| Label | Description |
|---|---|
| STD | Standard |
| HPR | High performance |
| HSK | Heat sink |

### Table 46. Thermal restriction matrix

| - | TDP | Number of Cores | Configuration 1: 4x3.5-inch SATA | Configuration 2: 8x3.5-inch SAS/SATA |
|---|---|---|---|---|
| | | | HSK/FAN type | HSK/FAN type |
| CPU TDP | 95 W | 8 | HPR/STD | HPR/STD |
| | 95 W | 6 | HPR/STD | HPR/STD |
| | 80 W | 8 | STD/STD | STD/STD |
| | 80 W | 6 | STD/STD | STD/STD |
| | 70 W | 4 | STD/STD | STD/STD |
| | 65 W | 8 | STD/STD | STD/STD |
| | 65 W | 6 | STD/STD | STD/STD |
| | 55 W | 4 | STD/STD | STD/STD |
| | 46 W | 2 | STD/STD | STD/STD |

**Table 46. Thermal restriction matrix (continued)**

| - | TDP | Number of Cores | Configuration 1: 4x3.5-inch SATA | Configuration 2: 8x3.5-inch SAS/SATA |
|---|---|---|---|---|
| | | | HSK/FAN type | HSK/FAN type |
| | 35 W | 2 | STD/STD | STD/STD |

**NOTE:** If BOSS or A2 GPU or a PCIe card >25 W and Broadcom 10 G NIC is installed, an HPR PCI fan and PCIe shroud are needed for both configurations.

# Thermal air restrictions

## ASHRAE A3/A4 environment

- The operating temperature is for a maximum altitude of 950 m for ASHRAE A3/A4 Cooling
- Redundant power supplies are required
- BOSS module is not supported
- Cooling redundancy is not supported due to single fan in the system (cooling zone is separated)
- A2 GPU is not supported
- Non-Dell qualified peripheral cards and /or peripheral cards greater than 25 W are not supported

14

# Appendix A. Standards compliance

The system conforms to the following industry standards.

**Table 47. Industry standard documents**

| Standard | URL for information and specifications |
|---|---|
| **ACPI**Advance Configuration and Power Interface Specification, v6.4 | ACPI |
| **Ethernet** IEEE Std 802.3-2022 | IEEE Standards |
| **MSFT WHQL** Microsoft Windows Hardware Quality Labs | Windows Hardware Compatibility Program |
| **IPMI** Intelligent Platform Management Interface, v2.0 | IPMI |
| **DDR5 Memory** DDR5 SDRAM Specification | JEDEC Standards |
| **PCI Express** PCI Express Base Specification, v5.0 | PCIe Specifications |
| **PMBus** Power System Management Protocol Specification, v1.2 | Power System Management Protocol Specification |
| **SAS** Serial Attached SCSI, 3 (SAS-3) (T10/INCITS 519) | SCSI Storage Interfaces |
| **SATA** Serial ATA Rev. 3.3 | SATA IO |
| **SMBIOS** System Management BIOS Reference Specification, v3.3.0 | DMTF SMBIOS |
| **TPM** Trusted Platform Module Specification, v1.2 and v2.0 | TPM Specifications |
| **UEFI** Unified Extensible Firmware Interface Specification, v2.7 | UEFI Specifications |
| **PI** Platform Initialization Specification, v1.7 | |
| **USB** Universal Serial Bus v2.0 and SuperSpeed v3.0 (USB 3.1 Gen1) | USB Implementers Forum, Inc. USB |
| **NVMe** Express Base Specification. Revision 2.0c | NVMe |
| **NVMe** Command Set Specifications<br>1. NVM Express NVM Command Set Specification. Revision 1.1c<br>2. NVM Express Zoned Namespaces Command Set. Revision 1.0c<br>3. NVM Express® Key Value Command Set. Revision 1.0c | |
| **NVMe** Transport Specifications<br>1. NVM Express over PCIe Transport. Revision 1.0c<br>2. NVM Express RDMA Transport Revision. 1.0b<br>3. NVM Express TCP Transport. Revision 1.0c | |
| **NVMe** NVM Express Management Interface. Revision 1.2c | |
| **NVMe** NVMe Boot Specification. Revision 1.0 | |

15

# Appendix C Additional resources

**Table 48. Additional resources**

| Resource | Description of contents | Location |
|---|---|---|
| Installation and Service Manual | This manual, available in PDF format, provides the following information:<br>• Chassis features<br>• System Setup program<br>• System indicator codes<br>• System BIOS<br>• Remove and replace procedures<br>• Diagnostics<br>• Jumpers and connectors | Dell.com/Support/Manuals |
| Getting Started Guide | This guide ships with the system, and is also available in PDF format. This guide provides the following information:<br>• Initial setup steps | Dell.com/Support/Manuals |
| System Information Label | The system information label documents the system board layout and system jumper settings. Text is minimized due to space limitations and translation considerations. The label size is standardized across platforms. | Inside the system chassis cover |
| Quick Resource Locator (QRL) | This code on the chassis can be scanned by a phone application to access additional information and resources for the server, including videos, reference materials, service tag information, and Dell contact information. | Inside the system chassis cover |
| Enterprise Infrastructure Planning Tool (EIPT) | The Dell online EIPT enables easier and more meaningful estimates to help you determine the most efficient configuration possible. Use EIPT to calculate the power consumption of your hardware, power infrastructure, and storage. | Dell.com/calc |